

 ISO 9001:2008 CERTIFIED	RISLONE TECHNICAL BULLETIN	
	Tech Bulletin #: TB-4701-2	Page 1 of 2
	Date 1 st Issued: September 15, 2008	Date Revised: December 8, 2010
	Rislone Fuel Injector Cleaner	Part #: 4701, 4732, 4701-5, 4701-55

FUEL INJECTOR CLEANER

Rislone High Performance Fuel Injector Cleaner with Upper Cylinder Lubricant is the best all-around fuel additive to use with every tank of fuel. This complete fuel system tune-up helps eliminate noisy injectors & fuel pumps, rough idle, hard starting and hesitation. High performance additives increase power, performance, mileage and help save gas by cleaning & lubricating fuel injectors.

- Regular use, summer and winter, maintains optimum efficiency and power.
- Smoothes rough idle and eliminates hard starts giving cleaner, quieter operation.
- Cleans fuel injectors, increases mileage and saves on high fuel costs at the pump.
- UCL, Upper Cylinder Lubricant, helps prevent cylinder, ring & piston wear along with lubricating valves & guides giving longer engine life.
- The Fuel Conditioner & Treatment protects and lubricates all parts of the fuel system including the fuel pump and injectors allowing more power & performance.
- Use with all gasoline, ULSD diesel, and E85 Flex-Fuel engines.
- Works with all unleaded, oxygenated, reformulated and bio fuels.
- Will not void manufacture's new vehicle warranty.
- Results will either be immediate or noticeable within a few days of driving. Non-solvent formula contains petroleum oils.



UCL - Upper Cylinder Lubricant

The Rislone UCL additive is specially designed to lubricate the upper cylinder of an engine; however this action starts in the fuel tank. This UCL formulation helps overcome the lack of lubrication in modern fuels including unleaded gasoline, ULSD diesel fuel, E85 Ethanol, and other oxygenated and bio fuels. In the fuel tank, UCL helps prevent rust & corrosion and this process continues into the fuel lines. UCL also lubricates and protects the fuel pump, giving it a longer life and quieter operation. The next step for the UCL formula is to lubricate the injectors allowing them to work more efficiently. Not only are cylinder deposits cleaned, including gum and varnish, but as the UCL treats the upper cylinder the lubricating film helps to prevent carbon from sticking so that it can be burned. This film completely lubricates the upper piston, rings, guides, valves, and seats.

DIRECTIONS / DOSAGE

P/N 4701 / 6 ounce bottle – Pour entire bottle into fuel tank. One bottle is concentrated to treat up to 25 gallons of gasoline or diesel fuel.

P/N 4732 / 32 ounce bottle – One bottle treats 100 gallons of gasoline or diesel fuel.

P/N 4701-5 / 5-gallon pail, 4701-55 / 55-gallon drum – Add approximately 3 ounces for every 10 gallons of fuel.

For vehicles with known fuel lubrication problems, double the dosage.

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel fuel motor vehicles and non-road engines.

Part Number:	4701	4732	4701-5	4701-55
UPC Item:	0 78615 04701 7	0 78615 04732 1	0 78615 04702 4	0 78615 04703 1
UPC Case:	1 00 78615 04701 4	1 00 78615 04732 8	N/A	N/A
Bottle Size:	6 FL. OZ. (177 mL)	32 FL.OZ. (472 mL)	5 Gallons	55 Gallons
Bottle Dimensions:	1.7 x 1.7 x 8.2	3.5 x 2.6 x 9.9	12.5 x 12.5 x 15	24 x 24 x 35
Bottle Cube:	24	90	2,344	20,160
Case Pack:	12 bottles per case	6 bottles per case	1 pail	1 drum
Case Size:	7.0 x 5.3 x 8.9	8.2 x 7.4 x 10.4	12.5 x 12.5 x 15	24 x 24 x 35
Case Cube:	330	631	2,344	20,160
Case Weight:	5.5 pounds	12.3 pounds	40 pounds	450 pounds
Pallet:	TI 47 HI 5 Total 235	TI 29 HI 4 Total 116	TI 9 HI 3 Total 27	TI 4 HI 1 Total 4
Pallet Height:	50 inches	48 inches	50 inches	40 inches
Tariff Code:	2710.19.3020	2710.19.3020	2710.19.3020	2710.19.3020