



RTF230

Rubber Tire Tractor



- Large Cab with 360° Visibility
- Road Speed up to 24 mph
- 180° Reversing Seat
- 3 Mode All-Wheel Steering
- Low Center of Gravity
- Stump Grinder and Mulcher Options



fecon.com
sales@fecon.com
+1 513 696 4430
800 528 3113

Technical Specifications

Fecon Bull Hog	BH120-3
R.O.P.S & F.O.P.S	Standard
Fuel Consumption	8-10 gph / 30 - 37 lph
Fuel Tank Capacity	48 gal / 225 ltr
Horsepower	230 hp / 168 kw
Engine Make / Model	Perkins 1106D-E66TA 6 cyl.
Max Torque @ RPM	714 ft lbs / 968Nm @ 1500 rpm
Overall Height	112" / 2844 mm
Length of Tractor Only	159" / 4038 mm
Length with Bull Hog & Winch	247" / 5257 mm
Weight of Tractor Only	13673 lbs / 6201 kg
Weight of Standard Bull Hog	4900 lbs / 2222 kg
Weight with Head & Winch	18573 lbs / 8423 kg
Width of Tractor Only	93.5" / 2375 mm
Width with BH120-3	100" / 2540 mm
Hi-Flow Circuit PSI / GPM	6000 psi / 75 gpm
Low Flow Circuit PSI / GPM	3000 psi / 26 gpm
Hydraulic Reservoir	84 gal / 320 ltr
Winch Capacity (line pull)	14000 lbs / 6350 kg
Rear View Camera	Optional
Turning Radius	14' 7" / 4445 mm
Tire Size	500 / 70-28
Travel Speed (low / hi)	0-24 mph / 0-40 kph
Ground Clearance	20" / 500 mm

Standard Machine Equipped with Rear Mount Blade and Hydraulic Winch



Fecon Performance on Rubber!

The 4x4 traction of the RTF230 with all wheel steering (AWS) provides agile handling and power to the ground for right of way maintenance, oil field clearing and vegetation management.

3 Modes of Steering



Capability for Stump Grinding and other Forestry Attachments



Large Cab Offers Comfort and Exceptional Visibility. Tilting Feature Allows for Easy Service and Maintenance Access



- Operator's cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options. • Safety Is The Responsibility Of The Operator.
- Specifications subject to change without notice. • Photographs may have been altered for marketing purposes.
- Always ensure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.



GS-30F-0019S